

NEW PRODUCTS



Trex-Onics® High-Flex Encoder Cable Your High Performance OEM Replacement

- 300 V
- Operating Temperature Range -40°C to 90°C
- AWM
- VW-1 Flame Rating
- UL Recognized in the U.S. & Canada
- RoHS Compliant

The next generation of servo motor and encoder cables is a single-cable solution combining power conductors with signal pairs and the data element of dedicated encoder cables. The convergence of multiple roles into a single-cable solution greatly simplifies inventory management, installation and maintenance. TPC's Trex-Onics® High-Flex Encoder Cable is built to withstand the harsh industrial environments that many motors operate; abrasion resistance and long flex-life are key physical characteristics protecting the innovative electrical properties of this exciting, composite, single-cable solution.

FEATURES & BENEFITS

1. FINELY-STRANDED COPPER CONDUCTORS —

Improves flexibility and extends conductor life in dynamic applications, color coded for ease of identification.

2. FILLERS — Low friction, non-wicking fillers increase flexibility in dynamic applications.

3. SPECIALLY COMPOUNDED TREX-ONICS® TPU JACKET

— Superior first line defense against oil, ozone, UV exposure and most chemicals, flame and heat resistant, all-weather flexibility.

4. OIL-RESISTANT INSULATION SYSTEM — Designed to provide a long flex-life for optimal drive performance.

5. HEAVY-DUTY 85% COVERAGE OF TINNED COPPER BRAID —

Provides a shield against EM and RF noise and interference. Designed for superior performance in moving applications.

6. SIGNAL PAIRS — Aluminum/polyester shielded for maximum flex-life and signal integrity.

7. DATA PAIRS — Low capacitance and aluminum/polyester shielded for maximum flex-life and signal integrity.

APPLICATIONS

- Robotics
- Encoders
- Motion Control
- Feedback Cable
- EnDat, Hiperface®, SSI
- Servo Motors

ENVIRONMENTS

- Abrasion
- Flexing
- Chemicals

LET TPC DO THE WORK.
GET YOUR CABLES CONNECTORIZED
& READY TO INSTALL.



ORDERING INFORMATION *(Call for pricing & availability)*

PART NO.	COMPOSITE CABLE	JACKET	POWER	DATA	SIGNAL	NOMINAL O.D.	WEIGHT/1000 FT
SC126747	16/1PR ISP + 24/2PR ISP + 22/5PR ISP	Green (RAL6018)	16 AWG	24 AWG	22 AWG	0.535"	145 LBS



TPC WIRE & CABLE CORP.
EXPECT HIGH PERFORMANCE®

TPC WIRE & CABLE CORP. HEADQUARTERS 9600 VALLEY VIEW RD, MACEDONIA, OHIO 44056
USA 800-521-7935 • FAX 866-528-2930 • CANADA 800-545-0122 • MEXICO 001-877-283-1696
CHILE 1230-020-0229 • COLOMBIA 0-1-800-915-7519 • PERU 0800-54863 • WWW.TPCWIRE.COM

WARRANTY AND DISCLAIMER: Seller makes no warranties, express or implied, with respect to this product, and seller disclaims any implied warranties of merchantability or fitness for any particular purpose. Further, seller will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profit) from any cause whatsoever.

TPC1534 (02/17) PRINTED IN U.S.A. ©Copyright 2017 by TPC Wire & Cable Corp. All rights reserved. No portion of this publication, whether in whole or in part, can be reproduced without the express written consent of TPC Wire & Cable Corp.



FS 35910