

# THERMO-TREX® 200 HD PROMO



**BUY \$3,000 WORTH OF THERMO-TREX® 200 HD SINGLE CONDUCTOR CABLE AND RECEIVE A FREE SMALL REEL RACK (part no. 12005)**



- UL Recognized / cUL
- CSA
- Operating Temperature Range -60°C to 200°C (-76°F to 392°F)
- Low Smoke Zero Halogen
- VW-1 Flame Rating
- 600 V

## FEATURES & BENEFITS

### 1. FLEXIBLE, TINNED COPPER STRANDING –

Increased flexibility for easier installation

### 2. SILICONE RUBBER INSULATION –

Provides resistance to heat, moisture and chemicals

### 3. WOVEN HIGH DENSITY FABRIC JACKET –

Superior abrasion and cut-through resistance

### 4. STAINLESS STEEL OVERBRAID –

Optional

## ORDERING INFORMATION

PART NO.	STOCK (FT) ON-HAND	AWG SIZE	CONDUCTOR STRANDING	AMPACITY*	NOMINAL O.D. (IN)	WT. (LBS) PER 1,000 '
441018BLK	LT = 4 weeks	18	7/26	27	0.12	11
441016BLK	<b>4,894</b>	16	7/24	37	0.2	25
441014BLK	<b>4,977</b>	14	7/22	51	0.22	30
441012BLK	<b>3,435</b>	12	19/25	66	0.24	40
441010BLK	<b>3,077</b>	10	19/23	90	0.27	50
441010WHT	<b>4,679</b>	10	19/23	90	0.27	50
441010RED	<b>9,745</b>	10	19/23	90	0.27	50
441008BLK	LT = 4 weeks	8	61/26	125	0.375	90
441006BLK	LT = 4 weeks	6	84/25	167	0.415	125
441004BLK	LT = 4 weeks	4	133/25	226	0.475	185
441002BLK	LT = 4 weeks	2	133/23	305	0.54	270
441001BLK	LT = 4 weeks	1	259/25	362	0.625	360
441100BLK	<b>1,033</b>	1/0	259/24	422	0.67	435
441200BLK	<b>920</b>	2/0	259/23	492	0.725	530
441300BLK	LT = 4 weeks	3/0	259/22	574	0.785	650
441400BLK	<b>1,285</b>	4/0	259/21	671	0.85	810
441250BLK	LT = 4 weeks	250	427/22	756	0.945	960
441350BLK	LT = 4 weeks	350	427/21	947	1.06	1310
441500BLK	LT = 4 weeks	500	427/19	1202	1.215	1830

*Ampacity\* is based on single conductor in free air, 200°C conductor temperature 40°C ambient temperature per IEEE STD 835  
LT = Lead Time*



**TPC WIRE & CABLE CORP.**  
EXPECT HIGH PERFORMANCE®

**TPC WIRE & CABLE CORP.** HEADQUARTERS 9600 VALLEY VIEW RD, MACEDONIA, OHIO 44056  
USA 800-521-7935 • FAX 866-528-2930 • CANADA 800-545-0122 • MEXICO 001-877-283-1696  
CHILE 1230-020-0229 • COLOMBIA 0-1-800-915-7519 • PERU 0800-54863 • [WWW.TPCWIRE.COM](http://WWW.TPCWIRE.COM)

**WARRANTY AND DISCLAIMER:** Seller makes no warranties, express or implied, with respect to this product, and seller disclaims any implied warranties of merchantability or fitness for any particular purpose. Further, seller will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profit) from any cause whatsoever.

TPC1441 (03/16) PRINTED IN U.S.A. ©Copyright 2016 by TPC Wire & Cable Corp. All rights reserved. No portion of this publication, whether in whole or in part, can be reproduced without the express written consent of TPC Wire & Cable Corp.



FS 35910