



Cable Glands

Grip-Seals® Heat & Chemically Resistant Cable Glands

Grip-Seals® Heat & Chemically Resistant Cable Glands operate up to 150°C, resist impact and corrosion, and provide exceptional gripping strength. It's an ideal accessory for use with our Chem-Gard® product line.

Ratings

Operating Temperature Range -35°C to 150°C

REACH Compliant

Enclosure Rating: NEMA 4X, NEMA 6, IP 68

Pressure Rating: 150 PSIG

Performance Characteristics

✓ Corrosion Resistant ✓ Liquid Tight Seal ✓ Extreme Temperature

Engineered to Resist

Flexing



Tension



High Temperature



Cold Temperature



Chemicals

Features & Benefits**Fluoroelastomer Form Seal**

Ensures a strong, uniform seal around the cord surface and will withstand high temperature conditions.

PVDF (Polyvinylidene Difluoride) Body Construction

Provides outstanding temperature and chemical resistance allowing for use at up to 150°C. Resists impact and corrosion and provides exceptional gripping strength. Ideal accessory for use with our Chem-Gard® product line.

Fluoroelastomer O-Ring and Nickel-Plated Brass Locking Nut

Provides uniform compression for a proper seal and withstands high temperature conditions. The nickel-plated brass locking nut included with each cable gland resists corrosion.

Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

| Part No. | Fitting Size | Cord O.D. Range |
|----------|--------------|-----------------|
| 55725 | 1/4 NPT | 0.08" - 0.20" |
| 55738 | 3/8 NPT | 0.08" - 0.24" |
| 55739 | 3/8 NPT | 0.16" - 0.31" |
| 55750 | 1/2 NPT | 0.24" - 0.47" |
| 55751 | 1/2 NPT | 0.39" - 0.55" |
| 55775 | 3/4 NPT | 0.51" - 0.71" |

