**Cable Glands** 

# **Grip-Seals® Nylon Cable Glands**

Each Grip-Seals® Nylon Cable Gland package includes the cable gland body, O-ring and locking nut. Our nylon friction ring provides uniform compression for a proper seal. It prevents bushing damage and results in a tight, uniform seal on the cord surface which seals out oil, chemicals and other contaminants. Our Grip-Seals Nylon Cable Glands are available in straight and 90° configurations.

<u>Cable Management</u>

RoHS **REACH** Compliant

Performance Characteristics ✓ Corrosion Resistant ✓ Liquid Tight Seal ✓ Straight and 90° Configurations ✓ Strain Relief

✓ Operating Temperature: -40°C to 107°C

M Flexing 🔢 Tension 👗 Chemicals

Engineered to Resist

Ratings

# Features & Benefits

### **Nylon Friction Ring**

Provides uniform compression for a proper seal. Prevents bushing damage and results in a tight, uniform seal on the cord surface.

#### **Multiple Synthetic Sealing Bushings Included with Each** Product

One part number covers a variety of cord diameters. Seals out water, oil, metal particles and other contaminants.

Security Yellow Nylon **Compression Nut and Threaded Body** 

Resists impact and corrosion. Provides exceptional gripping strength. Easy to remove and reuse. Sealing O-Ring

Seals out oil, chemicals and other contaminants.

# Ordering Information For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Part No.	Configuration	Fitting Size	Cord O.D. Range	Number of Bushings
55505	Straight	3/8" NPT	0.180" - 0.430"	4
55513	Straight	1/2" NPT	0.188" - 0.500"	5
55516	Straight	1/2" NPT	0.188" - 0.625"	7
55515	Straight	1/2" NPT	0.312" - 0.625"	5
555180	Straight	1/2" NPT	0.562" - 0.688"	1
55530	Straight	3/4" NPT	0.560" - 0.750"	2
555340	Straight	3/4" NPT	0.562" - 0.688"	1
55592	90°	1/2" NPT	0.188" - 0.625"	7
555189	90°	1/2" NPT	0.562" - 0.625"	5
555349	90°	3/4" NPT	0.562" - 0.688"	1
55593	90°	3/4" NPT	0.562" - 0.750"	2

