

## Cable Glands

## Kord-Gard® Stainless Steel Mesh Strain Relief

Kord-Gard® Stainless Steel Mesh Strain Relief Cable Glands have a 304 stainless steel smooth flange compression nut and threaded body ideal for washdown areas. Designed to fit tightly against panel surfaces to keep moisture and other contaminants out. Achieves IP68/NEMA4x rating. The partial double-weave stainless steel mesh is a unique drop-in basket design for easier assembly and provides exceptional gripping strength, longer cord life and corrosion resistance.



## Ratings



REACH Compliant

IP68 Rated

NEMA 4X Rated

## Performance Characteristics

✓ Extra Heavy-Duty Strain Relief ✓ Corrosion Resistant ✓ Extra Tight Seal ✓ Operating Temperature: -40°C to 121°C

## Engineered to Resist



Flexing



Tension



Chemicals

## Features &amp; Benefits

### Fully Double-Woven Stainless Steel Mesh

Provides exceptional gripping strength, extends cable life and resists corrosion.

### 304 Stainless Steel Smooth Flange Compression Nut and Threaded Body

Smooth flange compression nut eliminates crevices where bacteria can grow. Ideal for washdown areas. 304 Stainless Steel design resists impact and corrosion. Provides exceptional gripping strength. Easy to install.

### Multiple Synthetic Sealing Bushings Included with Each Product

One part number covers a variety of cord diameters. Seals out water, oil, metal particles and other contaminants.

### Sealing O-Ring

Designed to fit tightly against panel surface to keep moisture and other contaminants out of panel. Protects connections from corrosion.

## Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Part No.	Fitting Size	Cord O.D. Range	Number of Bushings
55310SS	3/8" NPT	0.188" - 0.310"	2
55311SS	3/8" NPT	0.310" - 0.440"	2
55320SS	1/2" NPT	0.370" - 0.500"	2
55321SS	1/2" NPT	0.500" - 0.570"	1
55330SS	3/4" NPT	0.560" - 0.690"	2
55343SS	1" NPT	0.688" - 0.875"	2
55341SS	1-1/4" NPT	0.875" - 1.250"	3
55319SS	1/2"	0.25" - 0.37"	2
55340SS	1"	0.625" - 0.75"	1
55313SS	1"	0.688" - 0.812"	1
55314SS	1"	0.750" - 0.875"	1
55315SS	1"	0.812" - 0.938"	1
55351SS	1-1/2"	0.875" - 1.375"	4
55333SS	2"	1.250" - 1.812"	4

