

Cable Tape

Vulko-Wrap™ Black Reinforced

Reinforced Vulko-Wrap™ has the same excellent properties as Vulko- $\mathsf{Wrap}^{\mathsf{TM}},$ but has been embedded with a glass yarn fiber braid for added strength while maintaining the flexibility. Reinforced Vulko-Wrap has a temperature rating of -60°F to +400°F and has a dielectric strength of 500 volts per mil. One roll has 36 feet of tape that is one inch wide. It is available in 40 mil thickness in the color black only.



MIL-I-22444C


Temperature Rating -60°F to 400°F

Performance Characteristics



Self-Vulcanizing

✓ High Dielectric Strength ✓ Reinforced with Glass Yarn Fiber













Features & Benefits

High Dielectric Strength

Effective for all electrical connections.

Specially Compounded, Synthetic Silicone Elastomer

Resistant to oil, water, ozone, and many chemicals as well as temperatures from -60°F to +400°F.

Reinforced With Glass Yarn Braid

Reinforcing braid embedded in the center of material provides enhanced mechanical strength while still allowing the product to cover irregular shapes.

Immediate Vulcanization

Requires no heat - becomes fully bonded in 24 hours at room temperature. Remains pliable over time.

Adhesive-Free

Easy to remove - leaves no residue. Covered fittings are immediately reusable.

40 Mil Thickness

Extra thick design allows wrapping over sharp and irregular surfaces without tearing or puncturing.

Ordering Information For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Part Number 1 Roll	Part Number 5 Roll Pack	Nominal Thickness	Nominal Width	Nominal Length	Wrap Color	Guideline Color	Dielectric Strength/Per Mil
18412	18412D	40 Mils	1 in. (2.54 cm)	36 ft (1100 cm)	Black	None	500 Volts

