


7 Pin Molded Valve Plugs

- RoHS Compliant
- Straight and 90° Configurations

The 7-Pin Molded Valve Plug is available in a straight or 90° head with no assembly required. Each connector head is protected with an O-ring seal and coupling nut with machined hole for tie down. Used with Atos, Moog, Vickers and Rexroth servo or proportional valves.



FEATURES & BENEFITS

1. TREX-ONICS® OVERALL SHIELDED CONTINUOUS FLEX MULTI-CONDUCTOR CABLE — Superior performance in continuous flex applications. TPC's unique cable 18/6* shielded design has been tested to over 25 million cycles without electrical failure.

2. O-RING SEAL — Each connector head is protected with an o-ring seal. The o-ring compresses when tightened, sealing the connector end from contaminants.

3. 90° OR STRAIGHT CONSTRUCTION — Select the proper configuration for the application.

4. PUR MOLDED HEAD DESIGN — Rugged polyurethane head is molded to the Trex-Onics® cable to provide a sealed connection, eliminating the risk of failure due to contaminants.

5. COUPLING NUT WITH MACHINED HOLE — Hole can be used to tie down coupling ring and eliminate possible loosening caused by vibration and constant movement. Insures a secure connection in the toughest environments.

6. THREAD — 7/8" – 20"

APPLICATIONS

- Used with Atos, Moog, Vickers and Rexroth servo or proportional valves.

ORDERING INFORMATION (MINIMUM PURCHASE MAY BE REQUIRED IF PRODUCT NOT STOCKED)

| PART NO. | | DESCRIPTION | LENGTH (FT) |
|----------|-------|-------------------|-------------|
| STRAIGHT | 90° | | |
| 77003 | 77903 | 7 Pin Female Plug | 3 |
| 77006 | 77906 | 7 Pin Female Plug | 6 |
| 77009 | 77909 | 7 Pin Female Plug | 9 |
| 77012 | 77912 | 7 Pin Female Plug | 12 |
| 77015 | 77915 | 7 Pin Female Plug | 15 |
| 77020 | 77920 | 7 Pin Female Plug | 20 |
| 77050 | 77950 | 7 Pin Female Plug | 50 |
| 77060 | 77960 | 7 Pin Female Plug | 60 |

* Part number 61406 page # 62