

# Build Your Own DeviceNet™ Flex-Net Cable Assemblies

| 1  | 2                                | 3                                   | 4        | 5   | 6  | 7   | 8  | 9                         |
|--|----------------------------------|-------------------------------------|----------|---|--|---|--|---------------------------|
| TYPE   | SIZE                             | ENDS                                | POLES    | HEAD CONFIGURATION                                  | CABLE  | UOM   | LENGTH   | COUPLING                  |
| <b>C</b>   | <b>P</b>                         | <b>1</b>                            | <b>5</b> | <b>E</b>  | <b>43</b>  | <b>M</b>  | <b>005</b>   |                           |
| <b>C =</b><br>Cord Set<br><br><b>R =</b><br>Receptacle | <b>P =</b><br>DeviceNet<br>Mini  | 1 = Single End                      |          | A = Male Straight                                   | <b>43 =</b> DeviceNet THIN #60007 High Performance Cable | Unit of Measure:<br><br><b>M =</b> Meters<br><br><b>F =</b> Feet<br><br><b>A =</b> Inches | Enter a three digit code in the box above.<br><br><b>EXAMPLE:</b><br><br><b>5 =</b> 005<br><br><b>50 =</b> 050<br><br><b>500 =</b> 500 | <b>Blank =</b><br>Regular |
|  |                                  | 2 = Double End                      |          | C = Female Straight                                 |  |   |  |                           |
|  | <b>T =</b><br>DeviceNet<br>Micro | E = Male Straight / Female Straight |          | <b>90° Plugs can only be made with Cable #60007</b> |  |   |  |                           |
|  |                                  | B = Male 90°                        |          |   |  |   |  |                           |
|  |                                  | D = Female 90°                      |          |   |  |   |  |                           |
|  |                                  | F = Male Straight to Female 90°     |          |   |  |   |  |                           |
|  |                                  | G = Male 90° to Female Straight     |          |   |  |   |  |                           |
|  |                                  | H = Male 90° to Female 90°          |          |   |  |   |  |                           |

Portable Cords  
 Power Cables (600 Volt to 35 kV)  
 Welding Cables  
 VFD/Servo Motor Cables  
 Reeling Cables  
 Control Cables/Instrumentation  
 Bus Cables  
 Flat Festoon Cables  
 Retractable Coil Cables  
 Chemical & Temp. Resistant Cables  
 High Temperature Cables  
 Igniter Cables  
 Thermocouple Extension Wires  
 Engineered Custom Cables