

## Cable Glands

## Grip-Seals® Stainless Steel Cable Glands

Grip-Seals® Stainless Steel Cable Glands have a 304 stainless steel smooth flange compression nut and threaded body ideal for washdown areas. Designed to fit tightly against panel surfaces to keep moisture and other contaminants out. Achieves IP68/NEMA4x rating.



## Ratings



IP68 Rated

NEMA 4X Rated

REACH Compliant

Operating Temperature: -40°C to 121°C

## Performance Characteristics

✓ Corrosion Resistant ✓ Extra Tight Seal ✓ 304 Stainless Steel ✓ Sealing O-Ring ✓ Strain Relief

## Engineered to Resist



Flexing



Tension



Chemicals

## Features &amp; Benefits

### 304 Stainless Steel Smooth Flange Compression Nut and Threaded Body

Smooth flange compression nut eliminates crevices where bacteria can grow. Ideal for washdown areas. 304 Stainless Steel design resists impact and corrosion. Provides exceptional gripping strength. Easy to install.

### Multiple Synthetic Sealing Bushings Included with Each Product

One part number covers a variety of cord diameters. Seals out water, oil, metal particles and other contaminants.

### Sealing O-Ring

Designed to fit tightly against panel surface to keep moisture and other contaminants out of panel. Protects connections from corrosion.

### Ordering Information

 For complete product ordering information, please scan the QR Code or contact your ATPC sales representative

Part No.	Fitting Size	Cord O.D. Range	Number of Bushings
55505SS	3/8" NPT	0.180" - 0.430"	4
55513SS	1/2" NPT	0.188" - 0.500"	5
55515SS	1/2" NPT	0.312" - 0.625"	5
55516SS	1/2" NPT	0.188" - 0.625"	7
55530SS	3/4" NPT	0.560" - 0.750"	2
55540SS	1" NPT	0.875" - 1.000"	1
55534SS	3/4"	0.688" - 0.812"	1
55531SS	1"	0.688" - 1.000"	4
55532SS	1-1/4"	0.875" - 1.375"	4
555331SS	2"	1.688" - 1.938"	2
55533SS	2"	1.250" - 1.810"	4

