

Mini Cordsets

Quick-Connex® Mini Cordsets - Quick-Lock Safety Device

Quick-Connex® Mini Cordsets - Quick-Lock Safety Device for use on ATPC size "A" size 3-6 Pole and "B" size 6-8 Pole. Disconnection is made impossible as this safety device prevents the accidental disconnection of power, warning the operator to shut down the power source before removing the Quick-Lock. Used with ATPC Quick-Connex® Mini cordsets, the Quick-Connex® Quick-Lock is UL Listed for Class I, Division 2 Hazardous Locations when sudden interruption of power can cause a safety issue.

For building cordsets with Quick-Connex® Quick-Lock for use in UL Listed Class I, Division 2 Hazardous Locations, follow the "Build Your Own Cordsets with Quick-Lock Assembly for Hazardous Locations" smart part instructions.

For added security, a Master Lock is available as an additional option, provided with two identical keys. Each lock is keyed differently.

**Ratings**

For Use in UL Hazardous Locations Class 1, Division 2

Performance Characteristics

✓ For Use as a Safety Lock-Out Device ✓ Operating Temperature: -20° to 90°C ✓ Oil Resistant

Features & Benefits**Prevents Accidental Disconnection of a ATPC Quick-Connex® Mini cordset in Class I, Division 2 Hazardous Locations**

When locked into place, the device cannot be disconnected, providing protection against unintentional separation of cable connection and power source.

Safe for Operator Use

Serves as a safety device, warning the operator to disconnect the power before removing.

Easy to Install

Lightweight and easy to lock into place on a connection. Installation instructions are included.

Applicable for Quick-Connex® Mini A and B size cordsets

For added security, Quick-Lock requires a tool for removal and is captive to the cable assembly with a wire tether.

Compatible with Master Lock

Quick-Connex® Quick-Lock can be used with Master Lock for guaranteed safety lock-out.

Master Lock is 1-3/16" wide, 3/16" diameter steel shackle with 4-pin cylinder

Scratch and corrosion resistant black vinyl body is tamper resistant to cutting and sawing, 4-pin cylinder, dual locking internal levers resist against prying.

Ordering Information

For complete product ordering information, please scan the QR Code or contact your ATPC sales representative

Part No. Description

84125 Quick-Connex® Quick-Lock Size A Mini - 3-6 Pole

84127 Quick-Connex® Quick-Lock Size B Mini - 6-8 Pole

84126 Master Lock

