

Cable Sleeving

Stainless Steel Flexible Tubing

Fully Interlocked Flexible Stainless Steel Tubing protects cable from damage due to sharp edges, metal chips, impact and abrasion in indoor and outdoor environments. Available in sizes from 0.25" inner diameter to 3" inner diameter to accommodate most cable sizes.

**Ratings**

High Temperature Resistance: 538°C (1000°F)

Performance Characteristics*

- ✓ Flame Resistance: Very Good
- ✓ Weld Spatter Resistance: Very Good
- ✓ Molten Splash Resistance: Very Good
- ✓ Flexibility: Excellent
- ✓ Abrasion Resistance: Excellent
- ✓ Water and Oil Resistance: Outstanding

Engineered to Resist

-  Flexing
-  Abrasion
-  Impact
-  Chemicals

Features & Benefits**Fully Interlocked Flexible Metal Tubing**

Protects cable from sharp edges, metal chips, impact and outdoor environments.

304 Grade Stainless Steel

Excellent protection against abrasion and mechanical abuse. Resists discoloration and rust.

Wall Thickness of 10-12 mils with 300 lbs. of Linear Break Strength

Provides defense against impact and abrasion.

Available in Multiple Diameters Ranging from 0.25" ID to 3.0" ID

Allows for selection of the right size sleeve for the application. Fits over most electrical cables and rubber or plastic hoses.

Ordering Information For complete product ordering information, please scan the QR Code or contact your ATPC sales representative

Part No.	Nominal Inner Diameter (in.)	Nominal O.D. (in.)	Inside Bending Diameter (in.)	Weight per 1,000 ft. (lbs.)
49320	1/4	0.375	3	11
49321	3/8	0.5	4	14
49322	1/2	0.625	6	16
49324	3/4	0.875	6-1/2	20
49325	1	1.13	7-1/2	28
49328	1-1/4	1.38	9-1/2	36
49330	1-1/2	1.65	11	48
49334	2	2.16	15	66
49342	3	3.16	22	102

**Notes**

*Performance Characteristics in increasing resistance ability: Moderate, Good, Very Good, Excellent, Outstanding