

CONNECTORS

SPEED-E CONNECTORS

Speed-E Connectors efficiently create a secure electrical connection. Replacing the role of wire nuts, push-in connectors require less motion and more easily creates a multi-wire splice. A color-coded clear shell offers visual verification of the connection. Rated 24amps, 105°C, 600V maximum for building wire and 1000V maximum for lighting fixtures/luminaires and signs, 22-12AWG Sol Cu / 18-12AWG Str Cu.



PART NO.	NO. OF POSITIONS	COLOR	DIMENSIONS		
			W (MM)	D (MM)	L (MM)
SPEEDE2	2	Yellow	10.8	7.7	16.5
SPEEDE3	3	Orange	10.1	7.7	16.5
SPEEDE4	4	Clear	19.4	7.7	16.5
SPEEDE5	5	Blue	23.7	7.7	16.5
SPEEDE8	8	Black	36.6	7.7	16.5

PARALLEL CONNECTORS



WIRE SIZE	NON-INSULATED	VINYL BUTTED SEAM FLARED	VINYL TUBULAR FLARED	NYLON STRAIGHT TUBULAR	NYLON FLARED BUTTED SEAM	NYLON FLARED TUBULAR	NYLON WINDOW WITH SLEEVE	HIGH TEMP 650°F	HIGH TEMP 900°F	HEAT SHRINK
22-16	AP/J	-	AFVP/J	ANP/J	-	AFNP	-	-	-	-
16-14	BP/J	-	BFVP/J	BNP/J	-	BFNP	-	BPNPT/J	-	-
12-10	DP/J	-	DFVP/J	DNP/J	-	DFNP	-	DPNPT/J	-	-
22-16	APC/J	AFVLP2	-	-	AFNPC	-	-	-	-	-
16-14	BPC/J	BFVLP	-	-	BFNPC	-	-	-	-	-
12-10	DPC/J	DFVLP	-	-	DFNPC/J	-	-	-	-	-

BUTT CONNECTORS



WIRE SIZE	NON-INSULATED	VINYL BUTTED SEAM FLARED	VINYL TUBULAR FLARED	NYLON STRAIGHT BUTTED SEAM	NYLON STRAIGHT TUBULAR	NYLON FLARED BUTTED SEAM	NYLON FLARED TUBULAR	NYLON WINDOW WITH SLEEVE	HIGH TEMP 650°F	HIGH TEMP 900°F	HEAT SHRINK
22-16	AC	AFVCWS	AFVC	ANCL	-	AFNC	AFNC/J	ANDCW	ACNPT	AWSCHT	HSC2216
16-14	BC	BFVCWS	BFVC	BNCL	-	BFNC/J	BFNC/J	BNDCW	BCNPT	BWS4HT	HSC1614
12-10	DC	CFVCWS	DFVC	DNCL	-	DFNC/J	DFNC/J	DNDCW	DCNPT	DWS4HT	HSC1210
26-22	EC	-	-	-	-	-	-	-	-	-	HSC2622

8-600MCM BUTT CONNECTORS



GAUGE	NON-INSULATED VINYL	INSULATED VINYL
8	C8R1	FVC8R1
6	C6R1	FVC6R1
4	C4R1	-
2	C2R1	-
1/0	C1/0R1	-
2/0	C2/0R1	-
3/0	C3/0R1	-
4/0	C4/0R1	-
300MCM	C150R1	-
350MCM	C200R1	-
500MCM	C250R1	-
600MCM	C300R1	-



8-500MCM PARALLEL CONNECTORS



GAUGE	PART NO.
8	P8R1
6	P6R1
4	P4R1
2	P2R1
1/0	P1/0R1
2/0	P2/0R1
3/0	P3/0R1
4/0	P4/0R1
250-300MCM	P150R1/J
350MCM	P250R1/J
400-500MCM	P300R1

SOLDERING TYPE HEAT SHRINKABLE BUTT CONNECTORS



		PART NO.	GAUGE	COLOR
•	•	HELA5-20	22-24 AWG	CLEAR
•	•	HELA5-16	18-20 AWG	RED
•	•	HELA5-14	14-16 AWG	BLUE
	•	HELA5-10	10-12 AWG	YELLOW

MALE BULLET CONNECTORS



WIRE SIZE	DIAMETER (IN)	VINYL FULLY INSULATED	VINYL FULLY INSULATED SUPPORT SLEEVE
22-16	0.156	AFVGMT5	AFVDGMT5
16-14	0.156	BFGMT5	BFVDGMT5
12-10	0.156	-	DFVD6MTSTOR

FEMALE BULLET CONNECTORS



WIRE SIZE	DIAMETER (IN)	VINYL FULLY INSULATED	VINYL FULLY INSULATED SUPPORT SLEEVE
22-16	0.156	ACVGFT5	ACVDGFT5
16-14	0.156	BCVGFT5	BCVDGFT5
16-14	0.195	-	BCVDGFT7
12-10	0.195	DCVGFT7	DCVDGFT7