



# NEW PRODUCT



## Releasable Speed-E Wire Connectors

- UL Listed
- CE
- RoHS Compliant
- REACH Compliant
- 600 volts max. building wire, 1000 volts max. in signs or luminaires
- Maximum Operating Temp 105°C

This lever type releasable connector is flame retardant and has a polycarbonate shell that is transparent for easy confirmation of wire insertion. It is available in 2-conductor, 3-conductor and 5-conductor connection styles. These connectors provide easy wire release and is a reusable wire connector.

### FEATURES & BENEFITS

- **WIDE WIRE RANGE** – 28 AWG – 14 AWG either solid or stranded conductors, 12 AWG only solid conductors
- **MULTIPLE LEVERS** – Easy wire release allowing it to be reusable
- **TRANSPARENT BODY** – Visual inspections of wire placement are made easy
- **FLAME RETARDANT** – UL 94V0 flame retardant polycarbonate material

### APPLICATIONS

- Appliance wiring
- Light fixtures
- Signs
- Building wiring

### ORDERING INFORMATION

MAXIMUM RECOMMENDED CURRENT		
PART NO.	PACK QTY	WIRE POSITIONS
RLS-SPEEDE2	500/bag 5,000/ctn	2
RLS-SPEEDE3	500/bag 5,000/ctn	3
RLS-SPEEDE5	300/bag 3000/ctn	5

