

Build Your Own Thermo-Trex® 500-Plus Cord Sets

16 AWG

1	2	3	4	5	6	7	8	9
TYPE	SIZE	ENDS	POLES	HEAD CONFIGURATION	CABLE	UOM	LENGTH	COUPLING
C	16 AWG	2	4	E	82	M	005	
C = Cord Set		1 = Single End	2	A = Male Straight	82 = 16/2 #41462	Unit of Measure:	Enter a three digit code in the box above. EXAMPLE: 5 = 005 50 = 050 500 = 500	Blank = Regular
R = Receptacle		2 = Double End	3	C = Female Straight	83 = 16/3 #41463	M = Meters		S = Stainless Steel
			4	E = Male Straight / Female Straight	84 = 16/4 #41464	F = Feet		
			5		85 = 16/5 #41465	A = Inches		

12 AWG

1	2	3	4	5	6	7	8	9
TYPE	SIZE	ENDS	POLES	HEAD CONFIGURATION	CABLE	UOM	LENGTH	COUPLING
C	12 AWG	2	4	E	89	M	005	
C = Cord Set		1 = Single End	3	A = Male Straight	89 = 12/3 #41423	Unit of Measure:	Enter a three digit code in the box above. EXAMPLE: 5 = 005 50 = 050 500 = 500	Blank = Regular
R = Receptacle		2 = Double End	4	C = Female Straight	90 = 12/4 #41424	M = Meters		S = Stainless Steel
			5	E = Male Straight / Female Straight		F = Feet		
						A = Inches		

Portable Cords
 Power Cables (600 Volt to 35 kV)
 Welding Cables
 VFD/Servo Motor Cables
 Reeling Cables
 Control Cables/Instrumentation
 Bus Cables
 Flat Festoon Cables
 Retractable Coil Cables
 Chemical & Temp. Resistant Cables
 High Temperature Cables
 Igniter Cables
 Thermocouple Extension Wires
 Engineered Custom Cables