

Gauge Size

535 KCMIL			
PRODUCT NAME	CABLE TYPE	NO. OF CONDUCTORS	PAGE
Super-Trex® Single Conductor Power Cable	Power	1	40
Super-Trex® Variable Frequency Drive Shielded Power Cable	VFD	3	48
646 KCMIL			
Super-Trex® Single Conductor Power Cable	Power	1	40
750 KCMIL			
Super-Trex® Medium Voltage Single Conductor Power Cable	Medium Voltage	1	43
777 KCMIL			
Super-Trex® Single Conductor Power Cable	Power	1	40

Ratings

RATING	PAGE
ANSI TIA/EIA 568-B	69-71
Antimicrobial	98
ASTM B-33	43
AWM	52, 70, 72
CE	49-50, 57-60, 79, 90
Corona Resistant to 2,000 V	48-50
CSA	29-31, 36-38, 46-47, 53, 56, 60-67, 93, 95-100, 108, 113
CSA – 1,000 V	49-50
cUL	32-33, 35, 48
Direct Burial	42
EIA RS-232/422/485	68
Extra Hard Usage	29-31, 33-36, 39
Extreme Usage	46-47
For CT Use	40
Frequency Range up to 500 MHz	69-70
Frequency Range up to 1000 MHz	69
FT-1 Flame Rating	30-32, 38, 46-47, 53, 56, 60-61, 67, 70, 93, 95-100
FT-2 Flame Rating	74, 114
FT-4 Flame Rating	29, 37, 40, 43, 48, 57-59, 77-79
FT-5 Flame Rating	33, 36
Halogen-Free Flame Retardant	69-70
ICEA S-75-381	33, 35
ICEA S-75-381/NEMA WC-58	43
IEC 60332-1	69-70
IEC 61156-5	70
IEC 61156-6	69
IEEE - 383 Flame Rating	43
IEEE 1202 Flame Rating	33, 40
ISO/IEC 11801	69-70

Ratings

RATING	PAGE
Low Smoke Zero Halogen	112, 114
MSHA Approved	29, 31, 33-36, 46, 53, 61, 65
ODVA Conformity	74, 77-85
RoHS Compliant	29-32, 37-40, 43, 46-47, 49-50, 53, 56-70, 72-87, 90-93, 95-103, 106-111, 113-117, 119-120
Suitable for Class 1, 2, Division 2	37, 53
Suitable for Class 1, 2, 3, Division 1 & 2	29-31, 33-36, 39
Sunlight Resistant	29, 40, 42, 49-50
TIA / EIA 568-C-2	70, 72
TIA / EIA 568-B-2 CAT6	71
Type PLTC	77-79
Type RHH/RHW	39-40
Type SC	46
Type SOOW	29-31
Type TC	56
Type TC – 600 V	37, 53
Type TC-ER	29, 48, 52
Type TC-ER – 600 V	49-50, 57, 59
Type TC-ER – 2,000 V	35
Type W	36
Type W – 2,000 V	33, 35, 39
Type WTTC – 1,000 V	53, 57-59
UL 2225	29
UL Listed	29-31, 33-37, 39-40, 46, 48-50, 52-53, 56-60, 84-85, 106, 119
UL Recognized	32, 38, 51-52, 61-68, 70, 72, 74-79, 90, 93, 95-100, 108, 110, 112-114
UV Resistant	29-35, 37, 39, 46-47, 53, 70
VW-1 Flame Rating	40, 52, 68, 93, 95-100, 112